

STP275 - 20/Wfw Superpoly. 0 50 100 150 200 250 300 0 2 4 6 8 10 12 0 10 20 30 40 Current (A) Power (W)
 Voltage(V) NMOT STP285-20/ Wfw STP280-20/ Wfw STP275-20/ Wfw Maximum Power at NMOT (Pmax)
 214.4 W 210.3 W 206.4 W Optimum Operating Voltage (Vmp) 39.8 V 39.5 V 39.2 V Optimum Operating
 Current (Imp) 7.20 A 7.14 A 7.07 A

STP280 - 20/Wfw STP275 - 20/Wfw STP270 - 20/Wfw 0/+5W Positive tolerance Positive tolerance of up to
 5 W delivers higher output reliability IP68 Rated Junction Box The Suntech IP68 rated junction box ensures an
 outstanding waterproof level, supports installations in all orientations and reduces stress on the cables. High
 reliable performance,

STP275-285 - 20 /Wfw-TG Wuxi Suntech Power Co., Ltd. Technology: Power Range: Wp Region: China
 Contact Manufacturer Product is no longer manufactured. Solar Panel MY Solar - M10 Series
 MY-M10/144-540-560W From EUR0.0616 / Wp ...

Suntech Power STP275-20/Wfw (5BB) - polykristallines Hochleistungssolarmodul mit 275 Watt in 5
 Busbar-Technologie Nennleistung: 275 W Leistungstoleranz: 0/+5W Länge x Breite x Höhe:
 1650 x 992 x 35 mm Frontabdeckung: ...

NOCT: Irradiance 800 W/m², ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class
 AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% STP275- 20/Wfw
 STP270 - 20/Wfw STP265 - 20/Wfw Temperature Characteristics Nominal Operating Cell Temperature
 (NOCT) 45±2°C Temperature Coefficient of Pmax -0.41 ...

Suntech STP275-20/Wfw 275Wp . Das Suntech STP275-20/ Wfw ist ein polykristallines Solarmodul mit
 275Wp. * neuer und unbenutzter Restposten * Module können leichte Lagerspuren aufweisen *
 Ersatzmodul für bestehende Anlagen zur Schadensregulierung bei Versicherungsällen!

Riesige Auswahl Suntech STP275-20/Wfw275Wp - PV-Module jetzt bei Secondsol bestellen. Registrieren.
 Anmelden. Benutzername. Passwort. 2-Faktor Anmeldung. Nach der Eingabe Ihres Benutzernamens erhalten
 Sie einen Code per E-Mail! ... STP275-20/Wfw 5.0 (123 Kundenrezensionen) 82,50 ...

Wfw STP275-20/ Wfw STP270-20/ Wfw Potenza massima in STC (Pmax) 280 W 275 W 270 W Tensione
 d"esercizio ottimale (Vmp) 31,3 V 31,2 V 31,1 V Corrente d"esercizio ottimale (Imp) 8,95 A 8,82 A 8,69 A
 Tensione a circuito aperto (Voc) 38,3 V 38,1 V 37,9 V Corrente di cortocircuito (Isc) 9,41 A 9,27 A 9,15 A

Painel solar fotovoltaico de 60 células, de excelente qualidade, policristalino, com uma potência
 de 275 Wp, com 5 busbar, de um dos fabricantes mais reconhecidos mundialmente pela sua qualidade,

inovação e fiabilidade. Tolerância positiva. Com estas características, proporciona a melhor relação preço/performance em instalações de autoconsumo fotovoltaico.

Achievers Energy STP270-280 - 20 /Wfw ?????????????? ... STP275-20/ Wfw ??? ???? 12 ? ??? 80.7%????25???? ?????????????? ????(Pmax) 275 Wp ??????????(Vmpp)

STP280 - 20/Wfw STP275 - 20/Wfw STP270 - 20/Wfw 0/+5W Positive tolerance Positive tolerance of up to 5 W delivers higher output reliability IP68 Rated Junction Box The Suntech IP68 rated junction box ensures an outstanding waterproof level, supports installations in all orientations and

NOCT: Irradiance 800 W/m², ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% STP275- 20/Wfw STP270 - 20/Wfw STP265 - 20/Wfw Temperature Characteristics Nominal Operating Cell Temperature (NOCT) 45±2°C Temperature Coeicient of Pmax -0.41 %/°C

NOCT: Irradiance 800 W/m², ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% STP280- 20/Wfw STP275 - 20/Wfw STP270 - 20/Wfw Temperature Characteristics Nominal Operating Cell Temperature (NOCT) 45±2°C Temperature Coefficient of Pmax -0.41 ...

Suntech STP275-20/Wfw = Suntech STP 275-20 / Wfw . Das Suntech STP275-20/ Wfw ist ein polykristallines Solarmodul mit 275Wp. * neuer und unbenutzter Restposten * Ersatzmodul für bestehende Anlagen zur Schadensregulierung bei Versicherungsfällen! * Preis gilt pro Modul * Lieferung oder Selbstabholung möglich; Bitte beachten!

Maksymalne zabezpieczenie 20 A Tolerancja mocy 0/+5 W STC: nas?onecznienie 1000W/m², temperatura modu?u 25?C AM =1,5; Najlepsze w klasie sprawdzane symulatorem solarnym klasy AAA (IEC 60904-9), dok?adno?? pomiarów od -3/+3% NOCT STP275-20/ Wfw STP270-20/ Wfw STP265-20/ Wfw Maksymalna moc przy NOCT (Pmax) 200.6 W 198 W 194 W

Wuxi Suntech Power Co., Ltd. Solarmodul Serie STP270-280 - 20 /Wfw. Ausführliches Profil mit Bilder, Zertifizierung und PDF von Hersteller ... STP270-20/ Wfw STP275-20/ Wfw STP280-20/ Wfw Garantie Produktgarantie 12 Jahre Leistungsgarantie 25 Jahre auf 80,7% der angegebenen Nennleistung Elektrische Daten bei STC

Web: <https://triceratech.co.za>